


Network Security

Chapter 2


Basics of Cryptography

- ❑ Overview Cryptographic Algorithms
- ❑ Attacking Cryptography
- ❑ Properties of Encryption Algorithms
- ❑ Classification of Encryption Algorithms




Cryptographic Algorithms: Overview

- ❑ During this course two main applications of cryptographic algorithms are of principal interest:
 - ❑ *Encryption* of data: transforms plaintext data into ciphertext in order to conceal its' meaning
 - ❑ *Signing* of data: computes a *check value* or *digital signature* to a given plain- or ciphertext, that can be verified by some or all entities being able to access the signed data
- ❑ Some cryptographic algorithms can be used for both purposes, some are only secure and / or efficient for one of them.
- ❑ Principal categories of cryptographic algorithms:
 - ❑ *Symmetric cryptography* using 1 key for en-/decryption or signing/checking
 - ❑ *Asymmetric cryptography* using 2 different keys for en-/decryption or signing/checking
 - ❑ *Cryptographic hash functions* using 0 keys (the “key” is not a separate input but “appended” to or “mixed” with the data).



Attacking Cryptography (1): Cryptanalysis

- ❑ *Cryptanalysis* is the process of attempting to discover the plaintext and / or the key
- ❑ Types of cryptanalysis:
 - ❑ *Ciphertext only*: specific patterns of the plaintext may remain in the ciphertext (frequencies of letters, digraphs, etc.)
 - ❑ *Known ciphertext / plaintext pairs*
 - ❑ *Chosen plaintext or chosen ciphertext*
 - ❑ *Differential cryptanalysis & linear cryptanalysis*
 - ❑ Newer development: *related key analysis*
- ❑ Cryptanalysis of public key cryptography:
 - ❑ The fact that one key is publicly exposed may be exploited
 - ❑ Public key cryptanalysis is more aimed at breaking the cryptosystem itself and is closer to pure mathematical research than to classical cryptanalysis
 - ❑ Important directions:
 - Computation of discrete logarithms
 - Factorization of large integers




Attacking Cryptography (2): Brute Force Attack

- ❑ The *brute force attack* tries every possible key until it finds an intelligible plaintext:
 - ❑ Every cryptographic algorithm can in theory be attacked by brute force
 - ❑ On average, half of all possible keys will have to be tried


Average Time Required for Exhaustive Key Search

Key Size [bit]	Number of keys	Time required at 1 encryption / μ s	Time required at 10^6 encryption / μ s
56	$2^{56} = 7.2 \times 10^{16}$	$2^{55} \mu$ s = 1142 years	10.01 hours
128	$2^{128} = 3.4 \times 10^{38}$	$2^{127} \mu$ s = 5.4×10^{24} years	5.4×10^{18} years
256	$2^{256} = 1.2 \times 10^{77}$	$2^{255} \mu$ s = 3.7×10^{63} years	3.7×10^{57} years



Reference Numbers Comparing Relative Magnitudes

Reference	Magnitude
Seconds in a year	$\approx 3 \times 10^7$
Seconds since creation of solar system	$\approx 2 \times 10^{17}$
Clock cycles per year (50 MHz computer)	$\approx 1.6 \times 10^{15}$
Binary strings of length 64	$2^{64} \approx 1.8 \times 10^{19}$
Binary strings of length 128	$2^{128} \approx 3.4 \times 10^{38}$
Binary strings of length 256	$2^{256} \approx 1.2 \times 10^{77}$
Number of 75-digit prime numbers	$\approx 5.2 \times 10^{72}$
Electrons in the universe	$\approx 8.37 \times 10^{77}$




Important Properties of Encryption Algorithms

Consider, a sender is encrypting plaintext messages P_1, P_2, \dots to ciphertext messages C_1, C_2, \dots

Then the following properties of the encryption algorithm are of special interest:

- ❑ **Error propagation** characterizes the effects of bit-errors during transmission of ciphertext to reconstructed plaintext P_1', P_2', \dots
 - ❑ Depending on the encryption algorithm there may be one or more erroneous bits in the reconstructed plaintext per erroneous ciphertext bit
- ❑ **Synchronization** characterizes the effects of lost ciphertext data units to the reconstructed plaintext
 - ❑ Some encryption algorithms can not recover from lost ciphertext and need therefore explicit re-synchronization in case of lost messages
 - ❑ Other algorithms do automatically re-synchronize after 0 to n (n depending on the algorithm) ciphertext bits



- ❑ The type of operations used for transforming plaintext to ciphertext:
 - ❑ *Substitution*, which maps each element in the plaintext (bit, letter, group of bits or letters) into another element
 - ❑ *Transposition*, which re-arranges elements in the plaintext
- ❑ The number of keys used:
 - ❑ *Symmetric ciphers*, which use the same key for en- / decryption
 - ❑ *Asymmetric ciphers*, which use different keys for en- / decryption
- ❑ The way in which the plaintext is processed:
 - ❑ *Stream ciphers* work on bit streams and encrypt one bit after another:
 - Many stream ciphers are based on the idea of linear feedback shift registers, and there have been detected vulnerabilities of a lot of algorithms of this class, as there exists a profound mathematical theory on this subject.
 - Most stream ciphers do not propagate errors but are sensible to loss of synchronization.
 - ❑ *Block ciphers* work on blocks of width b with b depending on the specific algorithm.

