



Fig. 9. Examples of real pressure patterns captured with the 16x16 sensor array. (a) These objects have been pushed down on the sensor with increasing weights in order to generate the input patterns, (b) The ADC voltage matrix measured with a mid range weight, (c) Result using the naive approximation ignoring parallel pathways in the matrix, (d) Results of the CNN approach showing improved and better fitting shapes of activation.

REFERENCES

- [1] H.-M. Gross, St. Mueller, Ch. Schroeter, M. Volkhardt, A. Scheidig, K. Debes, K. Richter, and N. Doering, "Robot companion for domestic health assistance: Implementation, test and case study under everyday conditions in private apartments," in *IEEE/RSJ Int. Conf. on Intelligent Robots and Systems (IROS)*. IEEE, 2015, pp. 5992–5999.
- [2] H.-M. Gross, A. Scheidig, St. Mueller, B. Schuetz, Ch. Fricke, and S. Meyer, "Sympartner: Living with a Sympathetic Robot Companion at Home - Findings from a 20-Weeks Field Trial with 20 Seniors" to appear in *proc. of IEEE International Conference on Robotics and Automation (ICRA) 2019*.
- [3] St. Mueller and H. M. Gross, "Making a socially assistive robot companion touch sensitive," in *Int. Conf. on Haptics and Touch Enabled Computer Applications (Eurohaptics)*. Springer, 2018, pp. 476–488.
- [4] St. Mueller, Ch. Schroeter, and H.-M. Gross, "Smart fur tactile sensor for a socially assistive mobile robot," in *Int. Conf. on Intelligent Robotics and Applications (ICIRA)*, ser. LNAI, vol. 9246, no. II. Springer, 2015, pp. 49–60.
- [5] L. Cang, P. Bucci, and K. E. MacLean, "Cuddlebits: friendly, low-cost furballs that respond to touch," in *Proc. of International Conference on Multimodal Interaction*. ACM, 2015, pp. 365–366.
- [6] X. L. Cang, P. Bucci, A. Strang, J. Allen, K. MacLean, and H. Liu, "Different strokes and different folks: Economical dynamic surface sensing and affect-related touch recognition," in *Proceedings of the 2015 ACM on International Conference on Multimodal Interaction*. ACM, 2015, pp. 147–154.
- [7] M. M. Jung, X. L. Cang, M. Poel, and K. E. MacLean, "Touch challenge'15: Recognizing social touch gestures," in *Proceedings of the 2015 ACM on International Conference on Multimodal Interaction*. ACM, 2015, pp. 387–390.
- [8] St. Mueller, Ch. Schroeter, and H.-M. Gross, "Low-cost whole-body touch interaction for manual motion control of a mobile service robot," in *Int. Conf. on Social Robotics (ICSR)*, ser. LNCS, vol. 8239. Springer, 2013, pp. 229–238.
- [9] J. Kim, M. Lee, H. J. Shim, R. Ghaffari, H. R. Cho, D. Son, Y. H. Jung, M. Soh, C. Choi, *et al.*, "Stretchable silicon nanoribbon electronics for skin prosthesis," *Nature communications*, vol. 5, p. 5747, 2014.
- [10] D. Silvera-Tawil, D. Rye, and M. Velonaki, "Artificial skin and tactile sensing for socially interactive robots: A review," *Robotics and Autonomous Systems*, vol. 63, pp. 230–243, 2015.
- [11] A. Schmeder and A. Freed, "Support vector machine learning for gesture signal estimation with a piezo-resistive fabric touch surface," in *NIME*, 2010, pp. 244–249.
- [12] Z. Pan, H. Cui, and Z. Zhu, "A flexible full-body tactile sensor of low cost and minimal connections," in *Systems, Man and Cybernetics, 2003. IEEE International Conference on*, vol. 3. IEEE, 2003, pp. 2368–2373.
- [13] L. Osborn, H. Nguyen, J. Betthausen, R. Kaliki, and N. Thakor, "Biologically inspired multi-layered synthetic skin for tactile feedback in prosthetic limbs," in *Engineering in Medicine and Biology Society (EMBC), 2016 IEEE 38th Annual International Conference of the*. IEEE, 2016, pp. 4622–4625.
- [14] G. Büscher, R. Köiva, C. Schürmann, R. Haschke, and H. J. Ritter, "Tactile dataglove with fabric-based sensors," in *Humanoid Robots (Humanoids), 2012 12th IEEE-RAS International Conference on*. IEEE, 2012, pp. 204–209.
- [15] H. C. Markham and B. R. Brewer, "Development of a skin for intuitive interaction with an assistive robot," in *Engineering in Medicine and Biology Society, 2009. EMBC 2009. IEEE, 2009*, pp. 5969–5972.
- [16] T. D'Alessio, "Measurement errors in the scanning of piezoresistive sensors arrays," *Sensors and Actuators A: Physical*, vol. 72, no. 1, pp. 71–76, 1999.
- [17] A. Freed, "Novel and forgotten current-steering techniques for resistive multitouch, duotouch, and polytouch position sensing with pressure," in *NIME*, 2009, pp. 230–235.
- [18] F. Yu and V. Koltun, "Multi-scale context aggregation by dilated convolutions," *arXiv preprint arXiv:1511.07122*, 2015.
- [19] V. Nair and G. E. Hinton, "Rectified linear units improve restricted boltzmann machines," in *Proceedings of the 27th international conference on machine learning (ICML-10)*, 2010, pp. 807–814.